

Aries 124

UV DTF Printer

Large-format UV sticker printer offering **precise detail and vibrant color.**



Scale Up Your Stickers



Ten channels for raised stickers.

CMYKW plus Light Cyan, Light Magenta, Light Black and Light Light Black, plus varnish, for an increased gamut and raised finish.



Four Epson i1600 printheads.

30 to 60 sq. ft. per hour at a 23.6" print width, which is production pace for UV DTF.



Print and laminate in one machine.

A 2-in-1 solution for permanent sticker application on rigid substrates.



White ink that stays ready.

WIMS prevents clogging, with active and passive auto-cleaning for reduced downtime.



Built-in filtration.

Filtration is integrated, so the machine runs on an open floor without separate ducting.

Support and warranty

- **Lifetime** DTF Station tech support
- **1-year limited warranty** on non-consumable parts
- **neoStampa RIP** included
- 2-in-1 print and laminate, no separate laminator

See it run. Contact your DTF Station dealer or visit dtfstation.com.

Contact Us



sales@dtfstation.com



(562) 573-1117



dtfstation.com



@dtfstation

Dealer Locator



Ten Channels, Raised Stickers.

Ten channels, raised finish.

The Aries 124 runs CMYK plus white plus Light Cyan, Light Magenta, Light Black and Light Light Black, plus varnish. The result is a wider gamut than a five channel UV machine and a genuinely raised sticker surface rather than a flat print.

Large format UV DTF.

Four Epson i1600 printheads cover a 23.6" width at 30 to 60 sq. ft. per hour. That is roughly five times the output of the Aries 213, for shops where UV DTF has stopped being a side line.

Integrated laminating.

Printing and laminating happen in the same pass, so permanent application to rigid substrates does not need a second machine or a second pair of hands.



Install & Facility

Dimensions (W x D x H)	88" x 45" x 65"
Machine Weight	720 lb (327 kg)
Power Supply	110 V
Rated Current	17.27 A
Power Consumption	1,900 W

Specifications

Printheads	(4) Epson i1600	Ink Management	WIMS white circulation
Max Print Width	23.6" (60 cm)	Printhead Cleaning	Auto, active and passive
Print Speed	30 to 60 sq. ft./h	Filtration	Built in
Ink Configuration	CMYKW + Lc, Lm, Lk, LLk + Varnish	User Interface	Touchscreen
Application	Rigid substrates	Software	neoStampa RIP
Laminating	Integrated, 2-in-1	Rated Current	17.27 A